

MINIMAG II

USB MAGNETIC STRIPE READER

The MiniMag™II Intelligent Reader delivers exceptional performance in brilliantly designed housing. It can read up to three tracks of magnetic stripe card data regardless of swiping direction or speed which increases usability. MiniMag's compact footprint is ideal for POS, security, loyalty and other applications where space is limited. The uniquely designed flat surface allows for mounting in different orientations using threaded inserts or Velcro®. The cable can exit through the side or bottom which provides flexibility in mounting options.



MINIMAG II SPECS

INTERFACE	Keyboard (PS/2), RS232, RS232 Port Powered, USB-KB, USB-HID, USB- CDC
POWER	+5 VDC, $\pm 10\%$, 50mV ripple maximum Keyboard (PS/2), 40mA maximum RS232, 70mA maximum USB-HID, USB-CDC, and USB-KB, 70mA maximum
CARD SPEED	5 to 65 ips (7.6 to 165 cm/s)
OPERATING TEMPS	32°F to 131°F (0°C to 55°C)
STORAGE TEMPS	-22°F to 158°F (-30°C to 70°C)
HUMIDITY	Maximum 95% non-condensing, dry storage
OPERATING LIFE	1,000,000 card swipes minimum
WARRANTY	One year, parts and labor
DIMENSION	3.54 inches (90 mm) x 1.34 inches (34 mm) x 1.10 inches (28 mm)
MEDIA THICKNESS	0.015 inches (0.381 mm) to 0.05 inches (1.27 mm)
MEDIA FORMATS	ISO 7811, AAMVA, and other F2F formats
SLOT WIDTH	0.040 inches (1.37 mm)
SWIPE SPEED	3 to 60 inches per second, bidirectional
WEIGHT	4.6 oz
INDICATORS	Tri-colored LED, beeper (excluding on port-powered model)
CABLE LENGTH	6-foot side exit cable (Bottom exit is an option)
CABLE CONNECTOR	Keyboard - 6 pin mini-DIN, RS232 DB9F, USB-Type A

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

